

4 Camera Input DVR



Power

Power Source
Consumption

19VDC
<42W

Video

Video Information
Video Compression
Video Input
Video Loop
Video Output

NTSC/ PAL (switch able)
MPEG4

4 channels. Composite video 1Vp- p 75WBNC

4 channels. Composite video 1Vp- p 75WBNC

Main monitor output: composite video 1Vp- p 75WBNC
monitor output: composite video 1Vp- p 75WBNC

D1: 720 * 480 pixels with 30IPS (NTSC)/720 * 576 pixels with 25IPS (PAL) CIF: 352 * 240 pixels with 120 IPS (NTSC) / 352 * 288 pixels with 100 IPS (PAL)

Maximum Recording Rate

D1: 30; 15; 7; 3 IPS (NTSC)/25; 12; 6; 3 IPS (PAL)

Recording Speed Increments

CIF: 120; 60; 30; 15 IPS (NTSC)/100; 50; 25; 12 IPS (PAL)

Image Quality

4 levels best; high; normal; basic

HDD Capacity

IDE type, ATA66, supported HDD * 1; support HDD capacity 500GB

HDD Quick Deletion

Quick clean up the "index system" of the recorded data files.
250GB 2 seconds

Recording Mode

Manual, Timer, Motion, Alarm, Remote

Refresh Rate

120 IPS (NTSC)/100 IPS (PAL)

Features

Audio I/O
Motion Detection Area
Motion Detection Sensitivity
Pre-alarm Recording
PTZ Control
Dwell Time
Alarm I/O
Digital Zoom
Key Lock
Video Loss Detection
Camera Title
Video Adjustment
Date Display Format
Operating Temperature
System Recovery
Optional Peripheral
External Dimensions
Weight

Single channel audio; input & output (mono)

16 * 12 grids per camera

4 levels

Yes (8MB)

Pelco-D (2400BPS)

Programmable with adjustable dwell time

4 inputs/1 output

2 x Zoom (live mode)

Yes

Yes

6 characters

Hue/Colour/Contrast/Brightness

YY/MM/DD; DD/MM/YY; MM/DD/YY or Off

10C ~ 40C (50F ~ 104F)

Auto recovery on power fail

Digital Video output requires VGA converter

343(w) x 59(h) x 223(d)mm

3.75Kg

Network

Back-up Device
Web Compression Format
Ethernet
Web Interface
Remote Alarm Notification
Network Connection

Network remote back-up

Motion JPEG

10/100 base-T; support remote control & live view via Ethernet

Support licensed software AP & IE browser

E-mailing images & uploading images to FTP sites specific account

Support TCP/IP, PPPoE, DHCP & DDNS function

Warranty

12 months

- Highly efficient MPEG4 DVR
- CIF & D1 record formats
- 100 IPS @ Cif
- 4 camera input compact unit
- Networking and remote back up
- Scheduled / Timed / Alarmed & VMD record modes